

Megaplex-4, Megaplex-2100/2104

HSF-1, HSF-2

Fiber Optic Teleprotection Modules



- Up to 10 × 64 kbps per fiber interface port connected to teleprotection equipment
- IEEE C37.94 compliance
- Single or dual optical link with 850 nm multimode fiber interface
- Simple configuration
- HSF-2 operation in all Megaplex chassis
- IEEE-1613 compliant option

The HSF-1 and HSF-2 modules comply with the IEEE C37.94 standard for up to 10 × 64 kbps optical fiber interfaces, thus enabling teleprotection equipment to utilize the advanced transport capabilities offered by Megaplex.

The modules feature a single- or dual-port fiber optic interface, operating at a nominal wavelength of 850 nm. Each port is terminated in a pair of ST connectors for connection to standard multimode fiber.

The fiber optic link operates at a nominal line rate of 2.048 Mbps and uses the framing mode specified in the IEEE C37.94 standard (based on the G.732N framing for E1 links).

In accordance with the IEEE C37.94 standard, each teleprotection payload channel occupies two timeslots on the HSF optical link, and is processed by the HSF module for transport via a single 64-kbps port. This increases the channel immunity to environmental disturbance and facilitates error correction. The HSF module optimizes each payload channel into a single 64-kbps timeslot over the E1/T1/SDH/SONET link, thus achieving 50% bandwidth saving over the transport network. In addition, the timeslots that do not carry the payload are suppressed and generated locally, assuring further bandwidth optimization over the transport network.

The fiber optic interface has a wide dynamic range, which ensures that the receiver will not saturate even when using short fiber optic cables (saturation is caused when the optical power applied to the receiver exceeds its maximum allowed input power, and results in very high bit error rates).

The receive path of the HSF optical port uses the clock signal recovered from the corresponding received line signal. The transmit path timing is derived from the nodal clock used by Megaplex. The user's teleprotection equipment should be set to loopback timing, that is, its link transmit clock should be locked to the receive clock derived from the receive data of the same port.

Specifications

TDM INTERFACES

Number of Ports

1 or 2

Compliance

Frame: IEEE C37.94

Connectors

Pair of ST connectors

Payload Rate (per port) $n \times 64$ kbps, where $n = 1$ to 10 (64 to 640 kbps)**Nominal Bit Rate**

2.048 Mbps

Wavelength

850 nm

Fiber Type

62.5/125 mm multimode

Transmitter Type

VSCSEL

Power Coupled into Fiber

-11 to -19 dBm (-15 dBm typical)



HSF-1, HSF-2

Fiber Optic Teleprotection Modules

Receiver Sensitivity

-32 dBm

Maximum Receiver Input Power

-11 dBm

Receiver Dynamic Range

21 dB

Range (Typical)

With 6.8 dB margin: 2 km/1.25 miles

With 3.4 dB margin: 4 km/2.5 miles

MANAGEMENT

Programmable via the Megaplex management system

TIMING

Internal Oscillator: ±30 ppm

GENERAL

Environment

Operating temperature: -10°C to 55°C

(14°F to 131°F)

Storage temperature: -20°C to +70°C

(-4°F to +158°F)

Humidity: up to 95%, non-condensing

Indicators

ALARM – On when a fault has been detected in the module

ON LINE – On when the link is operating properly and is active

LOC S. LOSS – On when the local module link has lost frame synchronization

REM S. LOSS – On when an indication of loss-of-frame synchronization is received by the module from the equipment connected to the remote end of the fiber optic link

TST – Reserved for future use

TST – Reserved for future use

Power Consumption

HSF-1: 8.0W

HSF-2: 9.0W

Ordering

RECOMMENDED CONFIGURATIONS

MP-2100M-HSF-1/ST/85

Single-port fiber optic teleprotection module for the MP-2100/2104 chassis


MP-2100M-HSF-2/ST/85

Dual-port fiber optic teleprotection module for the MP-2100/2104 and Megaplex-4 chassis

SPECIAL CONFIGURATIONS

Please contact your local RAD partner for additional configuration options

764-145-03/18 Specifications are subject to change without prior notice. © 1988-2018 RAD Data Communications Ltd. RAD products/technologies are protected by registered patents. To review specifically which product is covered by which patent, please see <http://rad.com>. The RAD name, logo, logo type, and the product names MIND, Optimum, Airmux, and Pnux, are registered trademarks of RAD Data Communications Ltd. All other trademarks are the property of their respective holders.



International Headquarters

24 Raoul Wallenberg Street
Tel Aviv 69719, Israel
Tel. 972-3-6458181
Fax 972-3-6498250, 6474436
E-mail market@rad.com

North America Headquarters

900 Corporate Drive
Mahwah, NJ 07430, USA
Tel. 201-5291100
Toll free 1-800-4447234
Fax 201-5295777
E-mail market@radusa.com

www.rad.com

Order this publication by Catalog No. 803690

