

Pluggable Transceivers

Small Form-Factor Pluggable Transceivers



SFP (Small Form-factor Pluggable) or SFP+/QSFP transceivers are hot-swappable optical and electrical transceiver units, each providing a different interface according to known compliance standards and pre-determined specifications. The units are plugged into host platforms to provide the required interface, thus enabling optimal combination of CAPEX and OPEX reduction, due to ease of network planning, management, maintenance, and stock flexibility.

RAD's Pluggable transceivers are fully compliant with the Multisource Agreement (MSA) specifications and are interoperable with third-party standards-based devices.

Built-in digital diagnostic monitoring (DDM) functionality is available for designated SFP types, allowing users to monitor the unit's transmitter optical output power, receiver input optical power, internal temperature, supply voltage and transmitter bias current levels in real-time.

The XFP and SFP+ are transceivers designed for 10G network applications.

QSFP28 transceiver modules are designed for use in 100 Gigabit Ethernet links.

QSFP+ transceiver modules are designed for use in 40 Gigabit Ethernet links.

QSFP-DD transceiver modules are designed for use in 400/800 Gigabit Ethernet links.

Pluggable Transceivers

Small Form-Factor Pluggable Transceivers

Specifications

The transmitter specifications are listed in the tables below:

- Fiber Optic Fast Ethernet/STM-1/STM-4 SFPs – see **Table 1**
- Fiber Optic Gigabit Ethernet SFPs – see **Table 2**
- Copper STM-1/Fast Ethernet/Gigabit Ethernet/10 Gigabit Ethernet SFP+ – see **Table 3**
- Fiber Optic 10 Gigabit Ethernet XFPs – see **Table 4**
- Fiber Optic 10 Gigabit Ethernet SFP+ – see **Table 5**
- Fiber Optic 40 Gigabit Ethernet QSFP+ – see **Table 6**
- Fiber Optic 100 Gigabit Ethernet QSFP28 – see **Table 7**
- Fiber Optic 25 Gigabit Ethernet SFP28 – see **Table 8**

Notes:

- *Commercial Pluggable Transceivers are designed to withstand temperatures between 0–70°C (32–158°F).*
- *Some of RAD's Pluggable Transceivers are available with extended temperature range between -20–85°C (-4–185°F) or in industrially hardened versions, designed to withstand temperatures between -40–85°C (-40–185°F).*
- *The operating humidity of the transceivers is 0 to 85%.*
- *The specified typical range may vary according to the specific product in which the SFP/XFP/SFP+/QSFP28 is used. For more information, refer to the data sheet of the specific product.*
- *All transceivers (customized and not customized) have been tested by RAD and approved as being compatible with other RAD*

Pluggable Transceivers

Small Form-Factor Pluggable Transceivers

Table 1. Fiber Optic Fast Ethernet/STM-1/STM-4 SFPs

Ordering Name, Interface, Connector	Wavelength, Fiber Type [nm], [μm]	Standards	Transmitter Type	Input Power [dBm]		Output Power [dBm]		Typical Max. Range	
				[min]	[max]	[min]	[max]	[km]	[miles]
SFP-2DH* Fast Ethernet/STM-1, LC	1310, 9/125 single mode	100BASE-LX10, IEEE 802.3 (FE), G.957 S1.1 (STM-1)	Laser	-28	-8	-15	-8	15	9.3
SFP-3D*, SFP-3H* Fast Ethernet/STM-1, LC	1310, 9/125 single mode	G.957 L1.1 (STM-1)	Laser	-34	-10	-5	0	40	24.8
SFP-10A Fast Ethernet/STM 1, LC	Tx - 1310 nm, Rx - 1550 nm, single mode (single fiber)	100BASE-BX, IEEE 802.3 (FE), G.957 S1.1 (STM-1)	Laser (WDM)	-34	-3	-14	-8	20	12.4
SFP-10AD*, SFP-10ADH* Fast Ethernet/STM-1, LC	Tx -1310/Rx -1550, 9/125 single mode (single fiber)	100BASE-BX10, IEEE 802.3 (FE) G.957 (STM-1)	Laser (WDM)	-28	-8	-14	-8	20	12.4
SFP-10BD*, SFP-10BDH* Fast Ethernet/STM-1, LC	Tx -1550/Rx -1310, 9/125 single mode (single fiber)	100BASE-BX10, IEEE 802.3 (FE) G.957 (STM-1)	Laser (WDM)	-28	-8	-14	-8	20	12.4
SFP-15DH* STM-4, LC	1310, 9/125 single mode	G.957 S4.1	Laser	-28	-8	-15	-8	15	9.3
SFP-16 STM-4, LC	1550, 9/125 single mode	G.957 L4.2	Laser	-28	-8	-3	+2	80	49.7
SFP-18A, SFP-18AED* Fast Ethernet/STM-1, LC	Tx -1310/Rx -1550, 9/125 single mode (single fiber)	-	Laser (WDM)	-28	-8	-5	0	40	24.8
SFP-18B, SFP-18BED* Fast Ethernet/STM-1, LC	Tx -1550/Rx -1310, 9/125 single mode (single fiber)	-	Laser (WDM)	-28	-8	-5	0	40	24.8
SFP-24 Fast Ethernet/STM-1, LC	850, 50/125 multimode	-	VCSEL	-25	-2	-10	-4	2	1.2
	850, 62.5/125 multimode	-	VCSEL	-25	-2	-10	-4	1	0.6

* **Legend:** **D** – internal DDM calibration; **H** – industrially hardened SFP -40–85°C (-40–185°F) & Humidity 0-85%; **ED** – external DDM calibration

Pluggable Transceivers

Small Form-Factor Pluggable Transceivers

Table 2. Fiber Optic Gigabit Ethernet SFPs

Ordering Name, Interface, Connector	Wavelength, Fiber Type		Standards	Transmitter Type	Input Power		Output Power		Typical Max. Range	
	[nm]	[μm]			[dBm] [min]	[max]	[dBm] [min]	[max]	[km]	[miles]
SFP-5D*, SFP-5DH*, SFP-5H* Gigabit Ethernet, LC	850, 50/125 multimode		1000BASE-SX, IEEE 802.3 (GbE)	VCSEL	-17	0	-9.5	0	0.55	0.3
SFP-6DH* Gigabit Ethernet, LC	1310, 9/125 single mode		1000BASE-LX10, IEEE 802.3 (GbE)	Laser	-20	-3	-9.5	-3	10	6.2
SFP-7DH* Gigabit Ethernet, LC	1550, 9/125 single mode		1000BASE-ZX (GbE)	Laser	-22	-3	0	+5	80	49.7
SFP-8D*, SFP-8DH* Gigabit Ethernet, LC	1310, 9/125 single mode		1000BASE-EX (GbE)	Laser	-21	-3	-4	+4	40	24.8
SFP-8D*, SFP-8DH* Gigabit Ethernet, LC	1310, 9/125 single mode		1000BASE-EX (GbE)	Laser	-21	-3	-4	+4	40	24.8
SFP-17AD*, SFP-17AH* Gigabit Ethernet, LC	Tx –1310/Rx –1490, 9/125 single mode (single fiber)		1000BASE-BX10, IEEE 802.3 (GbE)	Laser (WDM)	-20	-3	-9	-3	10	6.2
SFP-17BD*, SFP-17BH* Gigabit Ethernet, LC	Tx –1490/Rx –1310, 9/125 single mode (single fiber)		1000BASE-BX10, IEEE 802.3 (GbE)	Laser (WDM)	-20	-3	-9	-3	10	6.2
SFP-20, SFP-20EDH* Gigabit Ethernet, LC	1550, 9/125 single mode		1000BASE-EZX (GbE)	Laser	-32	-8	+1	+5	120	74.5
SFP-21A, SFP-21AED*, SFP-21AH* Gigabit Ethernet, LC	Tx –1310/Rx –1490, 9/125 single mode (single fiber)		1000BASE-BX, IEEE 802.3 (GbE)	Laser (WDM)	-24	-3	-5	0	40	24.8
SFP-21B, SFP-21BED*, SFP-21BH* Gigabit Ethernet, LC	Tx –1490/Rx –1310, 9/125 single mode (single fiber)		1000BASE-BX, IEEE 802.3 (GbE)	Laser (WDM)	-24	-3	-5	0	40	24.8
SFP-22ADH* Gigabit Ethernet, LC	Tx –1490/Rx –1570, 9/125 single mode (single fiber)		1000BASE-BX, IEEE 802.3 (GbE)	Laser (WDM)	-28	0	-3	+2	80	49.7
SFP-22BDH* Gigabit Ethernet, LC	Tx –1570/Rx –1490, 9/125 single mode (single fiber)		1000BASE-BX, IEEE 802.3 (GbE)	Laser (WDM)	-28	0	-3	+2	80	49.7
SFP-23A, SFP-23AED* Gigabit Ethernet, LC	Tx –1310/Rx –1550, 9/125 single mode (single fiber)		1000BASE-BX, IEEE 802.3 (GbE)	Laser (WDM)	-24	-3	-5	0	40	24.8
SFP-23B, SFP-23BED* Gigabit Ethernet, LC	Tx –1550/Rx –1310, 9/125 single mode (single fiber)		1000BASE-BX, IEEE 802.3 (GbE)	Laser (WDM)	-24	-3	-5	0	40	24.8
SFP-27DH* Gigabit Ethernet, LC	1270, 9/125 single mode		1000BASE-ZX (GbE)	Laser (CWDM)	-28	-3	0	+5	60	37.3
SFP-28A, SFP-28AD* Gigabit Ethernet, LC	Tx – 1310/Rx – 1550 9/125 single mode (single fiber)		1000BASE-BX10, IEEE 802.3 (GbE)	Laser (WDM)	-20	-3	-9	-3	10	6.2
SFP-28B, SFP-28BD* Gigabit Ethernet, LC	Tx – 1550/Rx –1310, 9/125 single mode (single fiber)		1000BASE-BX10, IEEE 802.3 (GbE)	Laser (WDM)	-20	-3	-9	-3	10	6.2
SFP-29DH* Gigabit Ethernet, LC	1290, 9/125 single mode		1000BASE-ZX (GbE)	Laser (CWDM)	-28	-3	0	+5	60	37.3
SFP-31DH* Gigabit Ethernet, LC	1310, 9/125 single mode		1000BASE-ZX (GbE)	Laser (CWDM)	-28	-3	0	+5	60	37.3
SFP-33DH* Gigabit Ethernet, LC	1330, 9/125 single mode		1000BASE-ZX (GbE)	Laser (CWDM)	-28	-3	0	+5	60	37.3

* **Legend:** **D** – internal DDM calibration; **H** – industrially hardened SFP -40–85°C (-40–185°F) & Humidity 0-85%; **ED** – external DDM calibration

Pluggable Transceivers

Small Form-Factor Pluggable Transceivers

Table 2 (Cont.) Fiber Optic Gigabit Ethernet SFPs

Ordering Name, Interface, Connector	Wavelength, Fiber Type		Standards	Transmitter Type	Input Power [dBm]		Output Power [dBm]		Typical Max. Range	
	[nm]	[μ m]			[min]	[max]	[min]	[max]	[km]	[miles]
SFP-35DH* Gigabit Ethernet, LC	1350, 9/125	single mode	1000BASE-ZX (GbE)	Laser (CWDM)	-28	-3	0	+5	60	37.3
SFP-37DH* Gigabit Ethernet, LC	1370, 9/125	single mode	1000BASE-ZX (GbE)	Laser (CWDM)	-28	-3	0	+5	60	37.3
SFP-41DH* Gigabit Ethernet, LC	1410, 9/125	single mode	1000BASE-ZX (GbE)	Laser (CWDM)	-28	-3	0	+5	60	37.3
SFP-43DH* Gigabit Ethernet, LC	1430, 9/125	single mode	1000BASE-ZX (GbE)	Laser (CWDM)	-28	-3	0	+5	60	37.3
SFP-45DH* Gigabit Ethernet, LC	1450, 9/125	single mode	1000BASE-ZX (GbE)	Laser (CWDM)	-28	-3	0	+5	60	37.3
SFP-47DH* Gigabit Ethernet, LC	1470, 9/125	single mode	1000BASE-ZX (GbE)	Laser (CWDM)	-24	-3	0	+5	80	49.7
SFP-49DH* Gigabit Ethernet, LC	1490, 9/125	single mode	1000BASE-ZX (GbE)	Laser (CWDM)	-24	-3	0	+5	80	49.7
SFP-51DH* Gigabit Ethernet, LC	1510, 9/125	single mode	1000BASE-ZX (GbE)	Laser (CWDM)	-24	-3	0	+5	80	49.7
SFP-53DH* Gigabit Ethernet, LC	1530, 9/125	single mode	1000BASE-BX, IEEE 802.3 (GbE)	Laser (CWDM)	-24	-3	0	+5	80	49.7
SFP-54DH* Multirate: Gigabit Ethernet, STM-4, STM-1, Fast Ethernet (multirate); LC	1310, 62.5/125	multimode	-	Laser	-18	-3	-9	-3	2	1.2
SFP-55DH* Gigabit Ethernet, LC	1550, 9/125	single mode	1000BASE-ZX (GbE)	Laser (CWDM)	-24	-3	0	+5	80	49.7
SFP-57DH* Gigabit Ethernet, LC	1570, 9/125	single mode	1000BASE-ZX (GbE)	Laser (CWDM)	-24	-3	0	+5	80	49.7
SFP-59DH* Gigabit Ethernet, LC	1590, 9/125	single mode	1000BASE-ZX (GbE)	Laser (CWDM)	-24	-3	0	+5	80	49.7
SFP-61DH* Gigabit Ethernet, LC	1610, 9/125	single mode	1000BASE-ZX (GbE)	Laser (CWDM)	-24	-3	0	+5	80	49.7
SFP-77ADH* Gigabit Ethernet, LC	Tx – 1310/Rx – 1490 9/125 single mode (single fiber)		1000BASE-BX, IEEE 802.3 (GbE)	Laser (WDM)	-26	-3	0	+5	60	37.3
SFP-77BDH* Gigabit Ethernet, LC	Tx – 1490/Rx – 1310 9/125 single mode (single fiber)		1000BASE-BX, IEEE 802.3 (GbE)	Laser (WDM)	-26	-3	0	+5	60	37.3
SFP-80ADH* Gigabit Ethernet, LC	Tx – 1490/Rx – 1550, 9/125 single mode (single fiber)		1000BASE-BX, IEEE 802.3 (GbE)	Laser (WDM)	-34	-8	2	6	140 (max. 36db link budget)	87
SFP-80BDH* Gigabit Ethernet, LC	Tx – 1550/Rx – 1490, 9/125 single mode (single fiber)		1000BASE-BX, IEEE 802.3 (GbE)	Laser (WDM)	-34	-8	2	6	140 (max. 36db link budget)	87

* **Legend:** **D** – internal DDM calibration; **H** – industrially hardened SFP -40–85°C (-40–185°F) & Humidity 0-85%;

Pluggable Transceivers

Small Form-Factor Pluggable Transceivers

Table 3. Fiber Optic 10 Gigabit Ethernet XFPs

Ordering Name, Interface, Connector	Wavelength, Fiber Type [nm], [μm]	Standards	Transmitter Type	Input Power [dBm]		Output Power [dBm]		Typical Max. Range	
				[min]	[max]	[min]	[max]	[km]	[miles]
XFP-1D*, XFP-1DH* 10 Gigabit Ethernet, LC	1310, 9/125 single mode	10GBASE-LR/LW IEEE 802.3	Laser	-14.4	+0.5	-8.2	+0.5	10	6.2
XFP-2D*, XFP-2DH* 10 Gigabit Ethernet, LC	1550, 9/125 single mode	10GBASE-ZR/ZW IEEE 802.3	Laser	-24	-7	0	+4	80	49.7
XFP-3D*, XFP-3DH* 10 Gigabit Ethernet, LC	1550, 9/125 single mode	10GBASE-ER/EW IEEE 802.3	Laser	-15.8	-1	-4.7	+4	40	24.8
XFP-4D* 10 Gigabit Ethernet, LC	850, 50/125 multimode	10GBASE-SR/SW IEEE 802.3	VCSEL	-9.9	-1	-7.3	-1	0.3	0.186
XFP-5D-17 to XFP-5D-61* 10 Gigabit Ethernet, LC	C-Band, Channels 17 to 61, 9/125 single mode	10GBASE-ER/EW IEEE 802.3 ITU grid, 100 GHz spacing, C-Band channels	Laser [DWDM]	-15.8	-1	-4.7	+4	40	24.8
XFP-7D-17 to XFP-7D-61* 10 Gigabit Ethernet, LC	C-Band, Channels 17 to 61, 9/125 single mode	10GBASE-ZR/ZW ITU grid, 100 GHz spacing, C-Band channels	Laser [DWDM]	-24	-7	-1	+4	80	49.7

* **Legend:** **D** – internal DDM calibration; **H** – industrially hardened SFP -40–85°C (-40–85°F) & Humidity 0-85%; **ED** – external DDM calibration

Table 4. Copper STM-1/Fast Ethernet/Gigabit Ethernet/10 Gigabit Ethernet SFP

Ordering Name, Interface, Connector	Standards	Cable Type	Impedance [Ω]	Typical Max. Range (Attenuation)	
				[m]	[ft]
SFP-30H* Gigabit Ethernet, RJ-45, SGMII Interface	10/100/1000BASE-T, IEEE 802.3	UTP, cat. 5	100	100	328
SFP-P-13 10 Gigabit Ethernet, RJ-45, SGMII Interface	100/1000BASE-T, IEEE 802.3	UTP, cat. 5e	100	100	328
	2.5GBASE-T, IEEE 802.3	UTP, cat. 5e		100	328
	5GBASE-T, IEEE 802.3	UTP, cat. 6		50	164
	10G BASE-T IEEE 802.3	UTP, cat. 6a		30	98

* **Legend:** **D** – internal DDM calibration; **H** – industrially hardened SFP -40–85°C (-40–185°F) & Humidity 0-85%

Pluggable Transceivers

Small Form-Factor Pluggable Transceivers

Table 5. Fiber Optic 10 Gigabit Ethernet SFP+

Ordering Name, Interface, Connector	Wavelength, Fiber Type [nm], [μm]	Standards	Transmitter Type	Input Power [dBm]		Output Power [dBm]		Typical Max. Range	
				[min]	[max]	[min]	[max]	[km]	[miles]
SFP-P-1DH* 10 Gigabit Ethernet, LC	1310nm, 9/125 single mode	10GBASE-LR/LW IEEE 802.3	Laser	-14.4	+0.5	-8.2	+0.5	10	6.2
SFP-P-2DH* 10 Gigabit Ethernet, LC	1550nm, 9/125 single mode	10GBASE-ZR/ZW	Laser	-24	-7	0	+4	80	49.7
SFP-P-3DH* 10 Gigabit Ethernet, LC	1550nm, 9/125 single mode	10GBASE-ER/EW IEEE 802.3	Laser	-15.8	-1	-4.7	+4	40	24.8
SFP-P-4DH* 10 Gigabit Ethernet, LC	850nm, 50/125 multimode	10GBASE-SR/SW IEEE 802.3	VCSEL	-9.9	-1	-7.3	-1	0.3	0.186
SFP-P-5ADH* 10 Gigabit Ethernet, LC	Tx – 1330 Rx – 1270 9/125 single mode (single fiber)	10GBASE-LR/LW IEEE 802.3	Laser (WDM)	-14	+0.5	-8.2	+0.5	10	6.2
SFP-P-5BDH* 10 Gigabit Ethernet, LC	Tx – 1270 Rx – 1330 9/125 single mode (single fiber)	10GBASE-LR/LW IEEE 802.3	Laser (WDM)	-14	+0.5	-8.2	+0.5	10	6.2
SFP-P-6DH* Multirate: 10 Gigabit Ethernet, Gigabit Ethernet; LC	1310nm, 9/125 single mode	10GBASE-LR/LW 1000BASE-LX10 IEEE 802.3	Laser	-14.4 -20	+0.5 -3	-8.2 -9.5	+0.5 -3	10 10	6.2 6.2
SFP-P-6ADH* 10 Gigabit Ethernet, LC	Tx - 1330nm, Rx – 1270nm 9/125 single mode (single fiber)	10GBASE-BX (10GbE)	Laser (WDM)	-15	+0.5	0	+6	40 (max. 15 db link budget)	24.8 (max. 15 db link budget)
SFP-P-6BDH* 10 Gigabit Ethernet, LC	Tx – 1270 nm, Rx - 1330nm, 9/125 single mode (single fiber)	10GBASE-BX (10GbE)	Laser (WDM)	-15	+0.5	0	+6	40 (max. 15 db link budget)	24.8 (max. 15 db link budget)
SFP-P-11DH-27-NR 10 Gigabit Ethernet, LC**	1555.75nm, 9/125 single mode	10GBASE-ZR/ZW (10G)	Laser (WDM CH 27, 192.7 THz)	-24	-7	0	+4.0	80 (max. 22 db link budget)	49.7 (max. 22 db link budget)
SFP-P-12AD 10 Gigabit Ethernet, LC	Tx – 1490 nm Rx – 1550 nm single mode (single fiber) DDMI	10GBASE-BX (10GbE)	Laser (EML)	-23	-6	-1	+4	80 (max. 22 db link budget)	49.7 (max. 22 db link budget)
SFP-P-12BD 10 Gigabit Ethernet, LC	Tx – 1550 nm Rx – 1490 nm single mode (single fiber) DDMI	10GBASE-BX (10GbE)	Laser (EML)	-23	-6	-1	+4	80 (max. 22 db link budget)	49.7 (max. 22 db link budget)

* Legend: D – internal DDM calibration; H – industrially hardened SFP -40–85°C (-40–185°F) & Humidity 0-85%

**Not RAD-customized

Pluggable Transceivers

Small Form-Factor Pluggable Transceivers

Table 6. Fiber Optic 40 Gigabit Ethernet QSFP+

Ordering Name, Interface, Connector	Wavelength, Fiber Type [nm], [μm]	Standards	Transmitter Type	Input Power [dBm]		Output Power [dBm]		Typical Max. Range	
				[min]	[max]	[min]	[max]	[km]	[miles]
QSFP-2D* 40 Gigabit Ethernet, MPO12****	850nm, 50/125 Multimode	40GBASE-SR4 IEEE 802.3	VCSEL	-9.5	+3.4	-7.6	+2.4	100/150***	62/93
QSFP-3D* 40 Gigabit Ethernet, LC****	1310	40GBASE-ER4 IEEE 802.3	Laser (CWDM)	-21.2*	-4.5	-2.7	+4.5	40	24.8

* **Legend:** D – internal DDM calibration
 **Average input power, each lane (min) is informative and not the principal indicator of signal strength.
 ***100m with OM3 MMF, 150m with OM4 MMF.
 ****Not RAD-customized

Pluggable Transceivers

Small Form-Factor Pluggable Transceivers

Table 7. Fiber Optic 100 Gigabit Ethernet QSFP28

Ordering Name, Interface, Connector	Wavelength, Fiber Type [nm], [μm]	Standards	Transmitter Type	Input Power [dBm]		Output Power [dBm]		Typical Max. Range	
				[min]	[max]	[min]	[max]	[km]	[miles]
QSFP28-1DH* 100 Gigabit Ethernet, LC, Internal Calibration	LAN-CWDM wavelengths 1295.56nm, 1300.05nm, 1304.58nm, 1309.14nm, 9/125 Single mode	100GBASE-LR4 IEEE 802.3	Laser EML	-10.6 **	+4.5	-4.3	+4.5	10	6.2
QSFP28-11DH* 100 Gigabit Ethernet, LC, Internal Calibration	1310nm PAM4, 9/125 Single mode	100GBASE-LR1 IEEE 802.3	Laser EML	-8.2**	+4.8	-1.9	+4.8	10	6.2
QSFP28-2D* , QSFP28-2DH* 100 Gigabit Ethernet, MPO12	850nm, 50/125 Multimode	100GBASE-SR4 IEEE 802.3	VCSEL	-10.3**	+2.4	-8.4	+2.4	0.1 Over OM4 fiber 0.07 Over OM3 fiber	0.06 0.04
QSFP28-4D	LAN-CWDM wavelengths 1295.56nm, 1300.05nm, 1304.58nm, 1309.14nm, 9/125 Single-mode	100G-4WDM-40	Laser EML	-20.5	-3.5	-2.5	6.5	40***	24.8
QSFP28-4DH-DML*	LAN-CWDM wavelengths 1295.56nm, 1300.05nm, 1304.58nm, 1309.14nm, 9/125 Single-mode	100G-4WDM-40	Laser DML	-20.5	-3.5	-2.5	6.5	40***	24.8
QSFP28-5DH*	LAN-WDM wavelengths 1295.56nm, 1300.05nm, 1304.58nm, 1309.14nm, 9/125 Single-mode	100GBASE-ZR4	Laser EML	-28	-7	8.0	12.5	80***	49.7

* **Legend:** **D** – internal DDM calibration; **H** – industrially hardened SFP -40–85°C (-40–185°F) & Humidity 0-85%

** Average input power, each lane (min) is informative and not the principal indicator of signal strength.

*** With FEC activated

****Not RAD-customized

Pluggable Transceivers

Small Form-Factor Pluggable Transceivers

Table 8. Fiber Optic 25 Gigabit Ethernet SFP28s

Ordering Name, Interface, Connector	Wavelength, Fiber Type [nm], [μm]	Standards	Transmitter Type	Input Power [dBm]		Output Power [dBm]		Typical Max. Range	
				[min]	[max]	[min]	[max]	[km]	[miles]
SFP28-1DH* 25 Gigabit Ethernet, LC	1310, 9/125 single mode	25GBASE-LR IEEE 802.3	Laser	-13.3	+2.0	-5.0	+2.0	10	6.2
SFP28-2DH* 25 Gigabit Ethernet, LC	850, OM4 multimode	25GBASE-SR IEEE 802.3	Laser	-10.3	+2.5	-8.4	+2.4	0.1	0.06

* **Legend:** **D** – internal DDM calibration; **H** – industrially hardened SFP -40–85°C (-40–85°F) & Humidity 0-85%

Pluggable Transceivers

Small Form-Factor Pluggable Transceivers

Ordering

To order an SFP/XFP/SFP+/QSFP+/QSFP28 unit, use its ordering name as listed in *Tables 1–8*.

Note: *It is strongly recommended to order RAD products with original RAD SFP/XFP/SFP+/QSFP+/QSFP28 installed. This will ensure that prior to shipping, RAD has performed comprehensive functional quality tests on the entire assembled unit, including the SFP/XFP/SFP+/QSFP28 devices.*

RAD cannot guarantee full compliance to product specifications for products using non-RAD SFPs/XFPs/SFP+s/QSFP28.

International Headquarters

24 Raoul Wallenberg St., Tel Aviv 6971923, Israel
Tel/Fax 972-52-4748272 | Fax 972-3-6498250
Email market@rad.com

North American Headquarters

900 Corporate Drive, Mahwah, NJ 07430, USA
Tel 201-529-1100 | Toll Free: 800-444-7234 | Fax: 201-529-5777
Email market@radusa.com



Your Network's Edge®

www.rad.com

127-100-02/26 Specifications are subject to change without prior notice. © 1988–2026 RAD Data Communications Ltd. RAD products/technologies are protected by registered patents. To review specifically which product is covered by which patent, please see ipr.rad.com. The RAD name, logo, logotype, and the product names MiNID, Optimux, Airmux, IPmux, and MiCLK are registered trademarks of RAD Data Communications Ltd. All other trademarks are the property of their respective holders.